



APPLICATION

Automotive Construction and Mining Swivel Joints Rotary

INTRODUCTION

K605 is a rotary pressure seals. We called it version *Premium Pro* because it is the best material over the world.

They can use in *extremely strict application* such as *Aerospace*, *Oil and Gas*, *Hammer*, *Quarry*.

It is designed specifically for use in hydraulic swivel joints with an internal rotary rod.

K605 is a best of range *high pressure and temperature performance*. KOLBEN UPA1003® is *superior excellent* material that used to *draconic* application. This is one of *best material* over the world.

MATERIAL

KOLBEN UPA1003®



FEATURES

Super excellent wear & abrasion resistance.

Easy installation.


Low compression

Low load at high speed, low noise

Super excellent resistance to extrusion and wear.

Extreme high extrusion resistance





Material	Application fluid	Temperature ⁰ C	Speed	Pressure	Max. Gap F
KOLBEN UPA1003®	Hydraulic oil 68	-50 to +160	≤ 1,0m/s	300 Bar	F ≤ 0,6 mm
	Grease Oil Brake Food		/ 4	350 Bar	F ≤ 0,5 mm
			1 2	500 Bar	F ≤ 0,4 mm
	Perfume Medical		12		

Rod Diamter	Groove Diameter	Seal Width	Groove Width
d (f7)	D (H9)	h	H +0.2
50	60	4.8	5
55	65	4.8	5
60	70	4.8	5
65	75	4.8	5
70	80	4.8	5
75	85	4.8	5
80	90	4.8	5

85	95	4.8	5
90	100	4.8	5
95	105	4.8	5
100	110	4.8	5
105	115	4.8	5
110	120	4.8	5
115	125	4.8	5
120	130	4.8	5
125	135	4.8	5
130	140	4.8	5
140	150	4.8	5
150	160	4.8	5